

Cisco Aironet 802.11A/B/G Wireless PCI Adapter

The Cisco® Aironet® 802.11a/b/g Wireless PCI Adapter provides high-performance 54-Mbps connectivity in the 2.4- and 5-GHz bands.

Whether configured to support single 802.11b coverage, single 802.11g coverage, single 802.11a coverage, dual-mode 802.11a/g coverage, or trimode 802.11a/b/g coverage, the Cisco Aironet 802.11a/b/g Wireless PCI Adapter is Wi-Fi compliant and combines the freedom of wireless connectivity with 802.11i/ Wi-Fi Protected Access 2 (WPA2) encryption for the performance, security, and manageability that businesses require (Figure 1).

The low-profile form factor and two-meter cable length provide significant flexibility for installation in low-profile devices, such as slim desktops and point-of-sale (POS) devices. For versatility, both a low profile and a standard profile bracket frame are included with the adapter. The attached dual-band, 2.4/5-GHz, 1-dBi effective gain antenna has a two-meter cable that enables optimal placement for maximum performance.

Figure 1. The Cisco Aironet 802.11a/b/g Wireless PCI Adapter



Enterprise-Class Security Solution

Designed with enterprise-class security requirements in mind, the Cisco Aironet 802.11a/b/g Wireless PCI Adapter uses the 802.1X standard for port-based network access. A full array of Extensible Authentication Protocol (EAP) types for user-based authentication, together with enterprise caliber Advanced Encryption Standard (AES) encryption, provide full 802.11i support. The adapter supports WPA2, the Wi-Fi Alliance certification for interoperable, standards-based wireless LAN security.

Support for Management Frame Protection (MFP) is now available on the Cisco Aironet 802.11a/b/g Wireless PCI Adapter. MFP adds security to the MAC management layer of 802.11 connectivity by cryptographically hashing the management frames and generating a Message Integrity Check (MIC) during network connection.

The Cisco Aironet 802.11a/b/g Wireless PCI Adapter supports the most common 802.1X authentication types, including EAP-Flexible Authentication via Secure Tunneling (EAP-FAST), Cisco LEAP, EAP-Transport Layer Security (EAP-TLS), Protected Extensible Authentication Protocol-Generic Token Card (PEAP-GTC), and PEAP-Microsoft Challenge Handshake Authentication Protocol version 2 (PEAP-MSCHAPv2). A wide selection of RADIUS servers, such as the Cisco Secure Access Control Server (ACS) and Cisco Access Registrar server, can be used for enterprise-class centralized user management that includes:

- Strong, mutual authentication to help ensure that only legitimate clients associate with legitimate and authorized network RADIUS servers via authorized access points
- Dynamic per-user, per-session encryption keys that automatically change on a configurable basis to protect the privacy of transmitted data
- Stronger encryption keys provided by Temporal Key Integrity Protocol (TKIP) enhancements such as message integrity check (MIC), per-packet keys via initialization vector hashing, and broadcast key rotation
- RADIUS accounting records for all authentication attempts
- IEEE 802.11i/WPA2 AES support

For more information on wireless security, visit <http://www.cisco.com/go/securewireless>.

Enhanced Client Network Management Features

A new and improved set of client utilities includes the Cisco Aironet Desktop Utility, System Tray Utility, and Client Administration Utility. Together, these utilities provide an intuitive graphical user interface (GUI) for easy configuration, monitoring, and management of the Cisco Aironet 802.11a/b/g Wireless PCI Adapter. Enhanced client network management features include:

- **Profile manager:** Allows users to create specific profile settings for various environments, making it simple for telecommuters and business travelers to move from one environment to another.
- **Customized profile settings:** Lets users individually select the channel, service set identifier (SSID), Wired Equivalent Privacy (WEP) key, and authentication method for different locations.
- **Cisco LEAP authentication status screen:** Provides status updates regarding the Cisco LEAP authentication process.
- **Auto-selection of profiles:** Provides automatic selection of established profiles, including those configured for EAP authentication, without requiring storage of the EAP username and password in the profile.
- **System tray icon:** Provides easy access to wireless LAN connection information and one-click access to common actions, such the manual selection a profile or turning the radio on or off.
- **Cisco Aironet Client Monitor:** Provides a subset of Cisco Aironet Desktop Utility features, such as status information about the client adapter and access to basic tasks (selecting a profile, for example). This application runs from the system tray icon.
- **Troubleshooting utility:** Provides step-by-step details on the process of connecting to an access point, as well as highlights on why a connection failed.
- **Support for the most popular enterprise operating systems:** Windows XP and Windows 2000.

- **Cisco Aironet Client Adapter installation wizard for Windows:** The wizard is provided for easy installation of the client firmware, drivers, and utilities and offers several installation options: install client utilities and driver; install driver only; or make driver installation diskette(s). For ease of use, the installation wizard image file is a self-extracting (.exe) file.

Features and Benefits

Table 1 lists the features and benefits of the Cisco Aironet 802.11a/b/g Wireless PCI Adapter.

Table 1. Product Features and Benefits

Feature	Benefit
Cisco Secure Wireless Solution	IEEE 802.1X support, including EAP-FAST, Cisco LEAP, PEAP-GTC, PEAP-MSCHAPv2, and EAP-TLS for mutual authentication with dynamic per-user, per-session encryption keys via TKIP enhancements. Full support for WPA and WPA2. Full support for Management Frame Protection (MFP).
Enhanced Client Network Management Features	Bundled with comprehensive, easy-to-use client network management utilities to provide a secure, intuitive, and convenient way to manage and configure the adapter.
Cisco LEAP Single Sign-on	Convenient option to use login credentials for LEAP sign-on on the user's network, eliminating the need to enter a second set of credentials.
Cisco Wireless Domain Services (WDS)	Cisco WDS is a collection of Cisco IOS® Software features that enhance wireless LAN client mobility and simplify wireless LAN deployment and management. Cisco WDS includes radio management aggregation, fast secure roaming, client tracking, and WAN link remote site survivability.

Product Specifications


Table 2 lists product specifications for the Cisco Aironet 802.11a/b/g Wireless PCI Adapter.

Table 2. Product Specifications

Feature	Description
Form Factor	<ul style="list-style-type: none"> • Standard and low-profile Type II PCI
Interface	<ul style="list-style-type: none"> • Standard PCI interface • PCI Rev. 2.3 compliant
Data Rates Supported	1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, 54 Mbps
Network Standard	IEEE 802.11a/b/g
Operating Voltage	3.3V (±0.3V)
LED	Status (green) and Activity (amber)
Media Access Protocol	Carrier-Sense Multiple Access with Collision Avoidance (CSMA/CA)
Wireless Medium	802.11g: <ul style="list-style-type: none"> • Direct Sequence-Spread Spectrum (DSSS) and Orthogonal Frequency Divisional Multiplexing (OFDM) 802.11a: <ul style="list-style-type: none"> • OFDM
Modulation	DSSS <ul style="list-style-type: none"> • Differential Binary Phase Shift Keying (DBPSK) @ 1 Mbps • Differential Quadrature Phase Shift Keying (DQPSK) @ 2 Mbps • Complementary Code Keying (CCK) @ 5.5 and 11 Mbps OFDM <ul style="list-style-type: none"> • BPSK @ 6 and 9 Mbps • QPSK @ 12 and 18 Mbps • 16-Quadrature Amplitude Modulation (QAM) @ 24 and 36 Mbps • 64-QAM @ 48 and 54 Mbps

Feature	Description				
Frequency Bands	<ul style="list-style-type: none"> • 2.40 to 2.4897 GHz • 5.15 to 5.35 GHz (FCC UNII 1 and UNII 2) • 5.725 to 5.85 GHz (FCC UNII 3) • 5.15 to 5.35 GHz (ETSI) • 5.47 to 5.725 (ETSI) • 5.15 to 5.25 GHz (Japan) 				
Delay Spread	<ul style="list-style-type: none"> • 350 ns @ 1 Mbps • 300 ns @ 2 Mbps • 200 ns @ 5.5 Mbps • 400 ns @ 6 Mbps • 250 ns @ 9 Mbps • 130 ns @ 11 Mbps • 250 ns @ 12 Mbps • 220 ns @ 18 Mbps • 160 ns @ 24 Mbps • 100 ns @ 36 Mbps • 90 ns @ 48 Mbps • 70 ns @ 54 Mbps 				
Receive Sensitivity 802.11g (typical)	<ul style="list-style-type: none"> • -94 dBm @ 1 Mbps • -93 dBm @ 2 Mbps • -92 dBm @ 5.5 Mbps • -86 dBm @ 6 Mbps • -86 dBm @ 9 Mbps • -90 dBm @ 11 Mbps • -86 dBm @ 12 Mbps • -86 dBm @ 18 Mbps • -84 dBm @ 24 Mbps • -80 dBm @ 36 Mbps • -75 dBm @ 48 Mbps • -71 dBm @ 54 Mbps 				
Receive Sensitivity 802.11a (typical)	5150 to 5250 MHz <ul style="list-style-type: none"> • -87 dBm @ 6 Mbps • -87 dBm @ 9 Mbps • -87 dBm @ 12 Mbps • -87 dBm @ 18 Mbps • -82 dBm @ 24 Mbps • -79 dBm @ 36 Mbps • -74 dBm @ 48 Mbps • -72 dBm @ 54 Mbps 				
Available Transmit Power Settings (Maximum power setting will vary according to individual country regulations.)	<table border="0"> <tr> <td> 802.11b/g: <ul style="list-style-type: none"> • 20 dBm (100 mW) @ 1, 2, 5.5, and 11 Mbps • 18 dBm (63 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, and 24 Mbps • 17 dBm (50 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, and 36 Mbps • 15 dBm (30 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, and 48 Mbps • 13 dBm (20 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps • 10 dBm (10 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps </td> <td> 5250 to 5350 MHz <ul style="list-style-type: none"> • -89 dBm @ 6 Mbps • -89 dBm @ 9 Mbps • -89 dBm @ 12 Mbps • -85 dBm @ 18 Mbps • -82 dBm @ 24 Mbps • -79 dBm @ 36 Mbps • -74 dBm @ 48 Mbps • -72 dBm @ 54 Mbps </td> <td> 5725 to 5805 MHz <ul style="list-style-type: none"> • -84 dBm @ 6 Mbps • -84 dBm @ 9 Mbps • -84 dBm @ 12 Mbps • -83 dBm @ 18 Mbps • -82 dBm @ 24 Mbps • -79 dBm @ 36 Mbps • -72 dBm @ 48 Mbps • -65 dBm @ 54 Mbps </td> <td> 5.470 to 5.725 GHz <ul style="list-style-type: none"> • -87 dBm @ 6 Mbps • -87 dBm @ 9 Mbps • -87 dBm @ 12 Mbps • -87 dBm @ 18 Mbps • -82 dBm @ 24 Mbps • -79 dBm @ 36 Mbps • -74 dBm @ 48 Mbps • -72 dBm @ 54 Mbps </td> </tr> </table>	802.11b/g: <ul style="list-style-type: none"> • 20 dBm (100 mW) @ 1, 2, 5.5, and 11 Mbps • 18 dBm (63 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, and 24 Mbps • 17 dBm (50 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, and 36 Mbps • 15 dBm (30 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, and 48 Mbps • 13 dBm (20 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps • 10 dBm (10 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps 	5250 to 5350 MHz <ul style="list-style-type: none"> • -89 dBm @ 6 Mbps • -89 dBm @ 9 Mbps • -89 dBm @ 12 Mbps • -85 dBm @ 18 Mbps • -82 dBm @ 24 Mbps • -79 dBm @ 36 Mbps • -74 dBm @ 48 Mbps • -72 dBm @ 54 Mbps 	5725 to 5805 MHz <ul style="list-style-type: none"> • -84 dBm @ 6 Mbps • -84 dBm @ 9 Mbps • -84 dBm @ 12 Mbps • -83 dBm @ 18 Mbps • -82 dBm @ 24 Mbps • -79 dBm @ 36 Mbps • -72 dBm @ 48 Mbps • -65 dBm @ 54 Mbps 	5.470 to 5.725 GHz <ul style="list-style-type: none"> • -87 dBm @ 6 Mbps • -87 dBm @ 9 Mbps • -87 dBm @ 12 Mbps • -87 dBm @ 18 Mbps • -82 dBm @ 24 Mbps • -79 dBm @ 36 Mbps • -74 dBm @ 48 Mbps • -72 dBm @ 54 Mbps
802.11b/g: <ul style="list-style-type: none"> • 20 dBm (100 mW) @ 1, 2, 5.5, and 11 Mbps • 18 dBm (63 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, and 24 Mbps • 17 dBm (50 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, and 36 Mbps • 15 dBm (30 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, and 48 Mbps • 13 dBm (20 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps • 10 dBm (10 mW) @ 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps 	5250 to 5350 MHz <ul style="list-style-type: none"> • -89 dBm @ 6 Mbps • -89 dBm @ 9 Mbps • -89 dBm @ 12 Mbps • -85 dBm @ 18 Mbps • -82 dBm @ 24 Mbps • -79 dBm @ 36 Mbps • -74 dBm @ 48 Mbps • -72 dBm @ 54 Mbps 	5725 to 5805 MHz <ul style="list-style-type: none"> • -84 dBm @ 6 Mbps • -84 dBm @ 9 Mbps • -84 dBm @ 12 Mbps • -83 dBm @ 18 Mbps • -82 dBm @ 24 Mbps • -79 dBm @ 36 Mbps • -72 dBm @ 48 Mbps • -65 dBm @ 54 Mbps 	5.470 to 5.725 GHz <ul style="list-style-type: none"> • -87 dBm @ 6 Mbps • -87 dBm @ 9 Mbps • -87 dBm @ 12 Mbps • -87 dBm @ 18 Mbps • -82 dBm @ 24 Mbps • -79 dBm @ 36 Mbps • -74 dBm @ 48 Mbps • -72 dBm @ 54 Mbps 		

Feature	Description			
Power Consumption Steady State	<ul style="list-style-type: none"> 802.11a 802.11b 802.11g 		802.11a: <ul style="list-style-type: none"> 16 dBm (40 mW) @ 6, 9, 12, 18, and 24 Mbps 14 dBm (25 mW) @ 6, 9, 12, 18, 24, and 36 Mbps 13 dBm (20 mW) @ 6, 9, 12, 18, 24, 36, 48, and 54 Mbps 11 dBm (13 mW) @ 6, 9, 12, 18, 24, 36, 48, and 54 Mbps 10 dBm (10 mW) @ 6, 9, 12, 18, 24, 36, 48, and 54 Mbps 	
Range (Typical with Cisco Aironet 802.11a/b/g Wireless CardBus Adapter at maximum transmit power communicating with a Cisco Aironet 1231 Access Point configured with a 2.2-dBi dipole antenna for 802.11b/g, and a 6-dBi gain patch for 802.11a.)	Indoor (typical) <ul style="list-style-type: none"> 54 Mbps 18 Mbps 11 Mbps 6 Mbps 1 Mbps 	Transmit: <ul style="list-style-type: none"> 554 mA maximum 539 mA maximum 530 mA maximum 	Receive: <ul style="list-style-type: none"> 318 mA maximum 327 mA maximum 282 mA maximum 	Standby: <ul style="list-style-type: none"> 203 mA average 203 mA average 203 mA average
Range (Typical with Cisco Aironet 802.11a/b/g Wireless CardBus Adapter at maximum transmit power communicating with a Cisco Aironet 1231 Access Point configured with a 2.2-dBi dipole antenna for 802.11b/g, and a 6 dBi gain patch for 802.11a.)	Outdoor (typical) <ul style="list-style-type: none"> 54 Mbps 18 Mbps 11 Mbps 6 Mbps 1 Mbps 	Transmit: <ul style="list-style-type: none"> 554 mA maximum 539 mA maximum 530 mA maximum 	Receive: <ul style="list-style-type: none"> 318 mA maximum 327 mA maximum 282 mA maximum 	Standby: <ul style="list-style-type: none"> 203 mA average 203 mA average 203 mA average
Range (Typical with Cisco Aironet 802.11a/b/g Wireless CardBus Adapter at maximum transmit power communicating with a Cisco Aironet 1231 Access Point configured with a 2.2-dBi dipole antenna for 802.11b/g, and a 6 dBi gain patch for 802.11a.)	Indoor (typical) <ul style="list-style-type: none"> 54 Mbps 18 Mbps 11 Mbps 6 Mbps 1 Mbps 	802.11b/g <ul style="list-style-type: none"> 45 ft (13 m) 110 ft (33 m) 165 ft (50 m) 	802.11b/g <ul style="list-style-type: none"> 90 ft (27 m) 180 ft (54m) 160 ft (48 m) 300 ft (91 m) 410 ft (124 m) 	
		802.11a <ul style="list-style-type: none"> 100 ft (30 m) 600 ft (183 m) 1000 ft (304 m) 	802.11b/g <ul style="list-style-type: none"> 250 ft (76 m) 600 ft (183 m) 1000 ft (304 m) 1300 ft (396 m) 2000 ft (610 m) 	
Compliance				
Safety	<ul style="list-style-type: none"> UL 60950 CSA 22.2 No. 60950 IEC 60950 EN 60950 			

Feature	Description
Radio Approvals	<ul style="list-style-type: none"> FCC Part 15.401-15.407 RSS-210 (Canada) EN 301.893 (Europe) ARIB STD-T71 (Japan) AS 4268.2 (Australia) FCC Part 15.247 RSS-210 (Canada) EN 300.328 (Europe) TELEC 33 and 66 (Japan) AS/NZS 3548 (Australia and New Zealand)
EMI and Susceptibility (Class B)	<ul style="list-style-type: none"> FCC Part 15.107 and 15.109 ICES-003 (Canada) VCCI (Japan) EN 301.489-1 and -17 (Europe)UL 60950
Other	<ul style="list-style-type: none"> IEEE 802.11a/b/g Cisco Compatible Wireless (based on Cisco Compatible Extensions v1.0, v2.0, v3.0 and v4.0) Wi-Fi WHQL FCC Bulletin OET-65C
Power Management	<p>Power management levels available:</p> <ul style="list-style-type: none"> CAM (Constantly Awake Mode) Fast PSP (Power Save Mode) Max PSP (Maximum Power Savings)FCC Part 15.107 and 15.109
Antenna	Integrated dual-band 2.4/5-GHz, 1-dBi, effective-gain antenna on a two-meter cable
Security Architecture Client Authentication	<p>Cisco Secure Wireless Solution supporting WPA and WPA2, including:</p> <p><i>Authentication</i></p> <ul style="list-style-type: none"> 802.1X support, including Cisco LEAP, EAP-FAST, PEAP-GTC, PEAP-MSCHAPv2), and EAP-TLS to yield mutual authentication and dynamic per-user, per-session encryption keys (WPA and WPA2) MAC address and standard 802.11 authentication mechanisms <p><i>Encryption</i></p> <ul style="list-style-type: none"> AES-Counter Mode with Cipher Block Chaining Message Authentication Code Protocol (CCMP) encryption (WPA2) TKIP encryption enhancements: key hashing (per-packet keying), message integrity check (MIC), and broadcast key rotation via Cisco TKIP or WPA TKIP Support for static and dynamic IEEE 802.11 WEP keys of 40 and 128 bits <p><i>Advanced Security</i></p> <ul style="list-style-type: none"> Support for Management Frame Protection (MFP)
Drivers	Microsoft Windows XP and Windows 2000
Dimensions	4.72 in. (119.9 mm) x 3.12205 in. (79.3 mm)
Weight	<ul style="list-style-type: none"> Standard (frame) PCI with antenna: 3.64 oz. (103.2 g) Standard (frame) PCI without antenna: 1.92 oz. (54.7 g) Low-profile PCI with antenna: 3.43 oz. (97.5 g) Low-profile PCI without antenna: 1.72 oz. (49.0 g)
Environmental	<p>Nonoperating (storage) temperature:</p> <ul style="list-style-type: none"> 0 to 85°C <p>Operating temperature:</p> <ul style="list-style-type: none"> 0 to 70°C <p>Humidity (noncondensing):</p> <ul style="list-style-type: none"> 10 to 90 percent
Warranty	One year
Wi-Fi Certification	

System Requirements

Table 3 lists system requirements for the Cisco Aironet 802.11a/b/g Wireless CardBus Adapter.

Table 3. System Requirements

Feature	Description
Compatible Interface	Standard and low-profile Type II PCI with standard PCI interface
Supported Operating Systems	Microsoft Windows XP and Windows 2000w

Ordering Information

Table 4 lists ordering information for the Cisco Aironet 802.11a/b/g Wireless PCI Adapter.

Customers are responsible for verifying approval for use in their individual countries. Please see <http://www.cisco.com/go/aironet/compliance> to verify approval and to identify the regulatory domain that corresponds to a particular country.

To place an order, visit the Cisco Ordering Website at <http://www.cisco.com/en/US/ordering/index.shtml>. Ordering Information

Table 4. Ordering Information

Product Name	Description
AIR-PI21AG-A-K9	Cisco Aironet 802.11a/b/g PCI Adapter; FCC configuration
AIR-PI21AG-A-K9-40	Cisco Aironet 802.11a/b/g PCI Adapter; FCC configuration (40-pack)
AIR-PI21AG-E-K9	Cisco Aironet 802.11a/b/g PCI Adapter; ETSI configuration
AIR-PI21AG-W-K9	Cisco Aironet 802.11a/b/g PCI Adapter; rest-of-world configuration
AIR-PI21AG-P-K9	Cisco Aironet 802.11a/b/g PCI Adapter; Japan2 configuration

Service and Support

Cisco offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco services, visit [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

For More Information

For more information about the Cisco Aironet 802.11a/b/g Wireless PCI Adapter, visit <http://www.cisco.com/go/wireless> or contact your local account representative.



Americas Headquarters:
 Cisco Systems, Inc.
 170 West Tasman Drive
 San Jose, CA 95134-1708
 USA
 www.cisco.com
 Tel: +1 (408) 553-4000
 Bld 885-N218 (S022)
 Fax: +1 (408) 553-0868

Asia Pacific Headquarters:
 Cisco Systems, Inc.
 160 Robinson Road
 #25-01 Central Tower
 Singapore 068913
 www.cisco.com
 Tel: +65 (65) 17 7777
 Fax: +65 (65) 17 7788

Europe Headquarters:
 Cisco Systems International BV
 Heisterbergpark
 Heisterbergweg 13-19
 1101 CH Amsterdam
 The Netherlands
 www.europe.cisco.com
 Tel: +31 (0) 20 090 0730
 Fax: +31 (0) 20 097 1000

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

©2007 Cisco Systems, Inc. All rights reserved. CCNY, the Cisco logo, and the Cisco Square Bridge logo are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and AccuSoft, Register, Aironet, BPA, Catalyst, CCA, CDDP, CDE, CUP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Employee/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, iPhone, IP TV, IQ Expertise, the IQ logo, IQ Net Readiness Scorecard, IQ Link Study, LightStream, Linksys, MeetingPlace, MGX, Networking Academy, Network Registrar, Packet, PIX, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0701R)